

VOLTEC

UPS

- Diseño de línea interactiva
- Batería fácil de reemplazar
- Fácil lectura de anunciador con LED
- Equipado con AVR (regulación automática de voltaje) para estabilizar el voltaje de entrada
- Proporciona protección contra rayos, transientes, sobrecargas y cortos circuitos
- Autoreiniciación al restablecimiento de AC
- Función de arranque en frío (Encendido DC)
- Supresión de transientes para teléfono, MODEM, fax e Internet
- Software opcional para guardar archivos abiertos antes de apagado automático



LUS
1000 VA

**Línea Interactiva
Con regulador de Voltaje**



Respaldo, Repuestos y Servicio Garantizados

www.voltecups.com

PLUS 1000VA

Especificaciones:

Model	EM	1000VA
Capacity	VA/Watts	1000VA/480W
Input	Voltage Frequency	110VAC,115VAC, 120VAC, 220VAC, 230 VAC or 240 VAC +25% /-25% 50 Hz or 60Hz +/-5%
Output	Voltage(Batt, Mode) Frequency Waveform Transfer time	110VAC,115VAC, 120VAC, 220VAC, 230 VAC or 240 VAC +/-10% 50 Hz or 60Hz +/-1Hz Modified sine wave Less than 4ms(typical)
Battery	Battery type Recharge time	12V/9AH x1PCS 5hours to 90 % of full capacity
Indicator	LED	LED indicator for line on, battery back-up, UPS cut-off
Alarm	Battery Back-up Battery Low Overload	Sounding every 3 seconds Sounding every1 second Continue beeping sound
Protection	Overload Short circuit Batt. Low cut-off	Fuse & current limited Fuse & current limited & cut-off No battery drain after cut-off
Physical	Dimension, D x W x H Net weight	290x95x170mm 7.5kgs
Environment	Operating Temperature Noise level	32° F-104 F at full load, 0-90% relative humidity (Non-Condensing) Less than 40db (at 1 meter)
Interface	Contact closure Software	DB9 connector for connecting with ups software RUPS 2000(Optional)

Rear Panel



1. INPUT: IEC type connector to connect the power cable.
2. AC Fuse: Protection against short-circuit electronic fuse.
3. Data line protection: Filtering of electrical noise on data transmission lines.
4. Communication port: Basic communication.
5. AC/Battery outputs: Output protected for critical loads that require additional electrical power.

TIEMPOS DE RESPALDO

EM-500VA	MONITOR DE 15" Y CPU	**** 15 MINUTOS
EM-650VA	MONITOR DE 15" Y CPU	**** 30 MINUTOS
1000VA	MONITOR DE 15" Y CPU	**** 45 MINUTOS



www.voltecups.com

VOLTEC
UPS

Vía Transístmica, Edif. Corona de Oro
Tel. (507) 261-4401
Fax. (507) 261-0741
ventas@voltecups.com